

# TECH 3



Machine for the cutting of bit, double bit keys and pump keys.

An extremely versatile key-cutting machine, easy to use and highly accurate, Tech 3 comes with interchangeable carriages which do not require gauging once they are installed.



\* Easy, reliable movement is provided by means of a system of horizontal levers. Clamps are self-centering, tempered and knurled.

\* The motor has two speeds to facilitate the cutting of various materials such as steel, brass, cast iron.

\* Tech 3 incorporates a double halogen lamp which can be positioned in any direction to provide perfect illumination of the work area.




Machine built to CE standards.




Double bit keys with vertical cuts	Double bit keys	Pump keys

## OPTIONAL

\* The CS carriage (D700745ZB) is specifically designed for making vertical cuts along the bit. It is easily fitted to the cutting machine and, with the addition of appropriate accessories, can be used for cutting Ford® Tibbe® type keys by code.




\* The CSP carriage (D704143ZB) is specially designed for rapid and accurate cutting of pump keys, including keys with extra thick bits.



Extremely easy to install, the carriage does not require gauging once it is fitted to the machine.

\* EUROPA carriage (D708990ZB): makes it possible to cut all pin and pipe single and double bit keys with great precision. Universal centering devices are provided with clamp, to ensure a perfect grip on bit and double bit pipe keys.



\* Raised base: the Tech 3 Europa CZ key machine has a lower support unit that raises the machine by approx 8 cm. This also acts as a swarf tray to collect filings. The raised base can also be fitted to the standard Tech 3.

# TECH 3



## TECHNICAL DATA

Motor:	single phase 220V/50Hz - Double speed - 4/8 poles - 0,24/0,18Kw
Cutting tools:	High speed steel (HSS), $\varnothing$ 80x1,5
Tracer point:	with micrometric regulation and spring
Jaws:	self-centering, tempered and knurled
Dimensions:	width 420 mm - depth 530 mm - height 300 mm
Weight:	45 Kg



## AVAILABLE VERSIONS

TECH 3	Code D809002ZB	TECH 3 EUROPA CZ	Code D809000ZB
TECH 3 EUROPA	Code D809001ZB	TECH 3 SKANDINAVIAN	Code D809610ZB